



Economy Glasswashers



Introducing the new Economy Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.

Economy Range
EG35
EG40



- **Fast**
- **Economical**
- **Robust**
- **Hygienic**



Performance

Fast two minute wash cycle
ensures maximum productivity

New innovative wash pump
increases wash pressure improving results

Rinse thermo-lock
delivers perfect rinse temperatures time after time

Energy and Cost Savings

New innovative wash pump
saves 180W per hour

Reduced water consumption
produces the optimum balance between water usage and hygiene

Improved rinse arms
increases initial response by 30% and rotation speed by 20%

Operation

Intuitive, simple controls
reduces user error and staff training

EasyClean filters
maintenance friendly filters protect critical components

Chemical auto-dosing
eliminates user intervention and prevents over or under dosing

Auto drain down (optional)
ensures rapid drain down with no need for user intervention

Integral water softener (optional)
softens water without the need for an external unit

'Welcome to a cleaner world'

Economy Range Glasswasher Specifications



| | EG35 | EG40 |
|--------------------------|--------------|--------------|
| Cycle time | 120 sec | 120 sec |
| Baskets (x2) | 350 x 350 mm | 400 x 400 mm |
| Height | 590 mm | 640 mm |
| Width | 415 mm | 465 mm |
| Depth | 465 mm | 510 mm |
| Depth with door open | 705 mm | 785 mm |
| Usable wash height | 205 mm | 240 mm |
| Drain height | 120 mm | 120 mm |
| Drain Ø | 25 mm | 25 mm |
| Wash tank | 11 lts | 14 lts |
| Boiler | 2.8 lts | 2.8 lts |
| Water usage | 2.4 lts p/c | 2.4 lts p/c |
| Wash element | 1.6 kW | 1.6 kW |
| Boiler element | 2.8 kW | 2.8 kW |
| Total load | 3 kW | 3 kW |
| Amps required | 13 Amps | 13 Amps |
| Detergent dosing | Yes | Yes |
| Rinse aid dosing | Yes | Yes |
| Water connection | 3/4 BSP | 3/4 BSP |
| Required water pressure | 2-4 bar | 2-4 bar |
| Required water flow rate | 10 lts p/min | 10 lts p/min |
| Drain pump | Optional | Optional |
| Internal softener* | Optional | Optional |

Where water hardness exceeds 100ppm a water softener is required.

*Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

