



# Standard Passthrough Dishwashers

Introducing the new Standard Range Passthrough from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



Standard  
Range  
SD900

- **Fast**
- **Powerful**
- **Energy Efficient**
- **Economical**



## Performance

**Fast, powerful wash cycle**  
for maximum productivity and deep cleaning

**Heavy duty heater elements**  
faster start up and improved heat recovery times

**Hood auto-start**  
increases speed and productivity and reduces user intervention

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

**Increased usable height**  
accommodates larger items such as trays, pots and utensils

## Energy and Cost Savings

**Low volume wash tank**  
reduces water consumption and chemical costs

**Reduced electrical costs**  
low water usage requires less energy to heat the machine

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

## Operation

**Intuitive, simple controls**  
reduces user error and staff training

**Counter balanced hood**  
makes loading and unloading easier for the operator

**Chemical auto-dosing (optional)**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit

**'Welcome to a cleaner world'**

## Standard Range Passthrough Specifications



18

### SD900

<b>Cycle time</b>	120/180 sec
<b>Baskets (x3)</b>	500 x 500 mm
<b>Height</b>	1480 mm
<b>Height - hood raised</b>	1930 mm
<b>Width</b>	640 mm
<b>Width including handle</b>	725 mm
<b>Depth</b>	885 mm
<b>Usable wash height</b>	405 mm
<b>Drain height</b>	470 mm
<b>Drain diameter Ø</b>	55 mm
<b>Wash tank</b>	22 lts
<b>Boiler</b>	5 lts
<b>Water usage</b>	2.4 lts p/c
<b>Wash element</b>	3.0 kW
<b>Boiler element</b>	6.0 kW
<b>Total load</b>	6.75 kW
<b>Amps required</b>	30 Amps*
<b>Detergent dosing</b>	Yes
<b>Rinse aid dosing</b>	Yes
<b>Water connection</b>	3/4 BSP
<b>Required water pressure</b>	2-4 bar
<b>Required water flow rate</b>	10 lts p/min
<b>Drain pump</b>	Optional
<b>Internal softener*</b>	Optional
<b>Break tank (WRAS)</b>	Optional



**Where water hardness exceeds 100ppm a water softener is required.**

\* Can be configured to operate on either 20A or 3Ph+N upon request.

\*\* Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



**DC Products**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

**t:** +44 (0)1749 870055 **f:** +44 (0)1749 870056 **e:** sales@dcproducts.co.uk **www.dcproducts.co.uk**

