Economy Passthrough Dishwashers

Introducing the new Economy Range Passthrough Dishwashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.

Economy Range
ED900

- **Fast**
- **Powerful**
- **Energy Efficient**
- **Economical**

Performance

Fast, powerful wash cycle
for maximum productivity and deep cleaning

Heavy duty heater elements
faster start up and improved heat recovery times

Hood auto-start
increases speed and productivity and reduces user intervention

Rinse thermolock
delivers perfect rinse temperatures time after time

Increased usable height
accommodates larger items such as trays, pots and utensils

Energy and Cost Savings

Low volume wash tank
reduces water consumption and chemical costs

Reduced electrical costs
low water usage requires less energy to heat the machine

Improved rinse arms
increases initial response by 30% and rotation speed by 20%

Operation

Intuitive, simple controls
reduces user error and staff training

Counter balanced hood
makes loading and unloading easier for the operator

Chemical auto-dosing (optional)
eliminates user intervention and prevents over or under dosing

Auto drain down (optional)
ensures rapid drain down with no need for user intervention

Integral water softener (optional)
softens water without the need for an external unit

Economy Range Passthrough Specifications

	ED900
Cycle time	60/120/180 sec
Baskets (x3)	500 x 500 mm
Height	1500 mm
Height - hood raised	1930 mm
Width	655 mm
Width including handle	725 mm
Depth	745 mm
Usable wash height	400 mm
Drain height	470 mm
Drain diameter Ø	32 mm
Wash tank	22 lts
Boiler	5 lts
Water usage	2.6 lts p/c
Wash element	3.0 kW
Boiler element	6.0 kW
Total load	6.75 kW
Amps required	32 Amps*
Detergent dosing	Yes
Rinse aid dosing	Yes
Water connection	3⁄4 BSP
Required water pressure	2-4 bar
Required water flow rate	10 lts p/min
Drain pump	Optional
Internal softener*	Optional
Break tank (WRAS)	Optional

Where water hardness exceeds 100ppm a water softener is required.

* Can be configured to operate on either 20A or 3Ph+N upon request.

** Internal water softener is not suitable for hot water above 30˚C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.

DC Products
Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY
t: +44 (0)1749 870055 **f:** +44 (0)1749 870056 **e:** sales@dcproducts.co.uk **www.dcproducts.co.uk**