



# Economy Glasswashers



Introducing the new Economy Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



**Economy Range**  
EG35  
EG40  
EG50

- **Fast**
- **Economical**
- **Robust**
- **Hygienic**



## Performance

**Fast two minute wash cycle**  
ensures maximum productivity

**New innovative wash pump**  
increases wash pressure improving results

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

## Energy and Cost Savings

**New innovative wash pump**  
saves 180W per hour

**Reduced water consumption**  
produces the optimum balance between water usage and hygiene

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

## Operation

**Intuitive, simple controls**  
reduces user error and staff training

**EasyClean filters**  
maintenance friendly filters protect critical components

**Chemical auto-dosing**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit

**'Welcome to a cleaner world'**

## Economy Range Glasswasher Specifications



	EG35	EG40	EG50
<b>Cycle time</b>	120 sec	120 sec	180 sec
<b>Baskets (x2)</b>	350 x 350 mm	400 x 400 mm	500 x 500 mm
<b>Height</b>	590 mm	640 mm	830 mm
<b>Width</b>	415 mm	465 mm	565 mm
<b>Depth</b>	465 mm	510 mm	610 mm
<b>Depth with door open</b>	705 mm	785 mm	995 mm
<b>Usable wash height</b>	205 mm	240 mm	305 mm
<b>Drain height</b>	120 mm	120 mm	150 mm
<b>Drain Ø</b>	25 mm	25 mm	25 mm
<b>Wash tank</b>	11 lts	14 lts	26 lts
<b>Boiler</b>	2.8 lts	2.8 lts	2.8 lts
<b>Water usage</b>	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c
<b>Wash element</b>	1.6 kW	1.6 kW	2.0 kW
<b>Boiler element</b>	2.8 kW	2.8 kW	6.0 kW
<b>Total load</b>	3 kW	3 kW	6.4 kW
<b>Amps required</b>	13 Amps	13 Amps	13 or 30 Amps
<b>Detergent dosing</b>	Yes	Yes	Yes
<b>Rinse aid dosing</b>	Yes	Yes	Yes
<b>Water connection</b>	3/4 BSP	3/4 BSP	3/4 BSP
<b>Required water pressure</b>	2-4 bar	2-4 bar	2-4 bar
<b>Required water flow rate</b>	10 lts p/min	10 lts p/min	10 lts p/min
<b>Drain pump</b>	Optional	Optional	Optional
<b>Internal softener*</b>	Optional	Optional	Optional

**Where water hardness exceeds 100ppm a water softener is required.**

\*Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



**DC Products**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk [www.dcprouducts.co.uk](http://www.dcprouducts.co.uk)

