



Standard Extra Glasswashers

Introducing the new Standard Extra Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



Standard Extra Range

SXG40
SXG45
SXG50

- **Fast**
- **Economical**
- **Energy Efficient**
- **Space Saving**



Performance

My Wash cycle

four fixed and one self configurable cycles

New innovative wash pump

increases wash pressure improving results

Hydrodynamic basket slides

ensures optimum wash and rinse coverage

Rinse thermo-lock

delivers perfect rinse temperatures time after time

Dual element configuration

for faster start up and guaranteed wash temperatures

Energy and Cost Savings

Double skinned cabinet door

reduces noise and heat emissions whilst lowering running costs

Reduced water consumption

produces the optimum balance between water usage and hygiene

Improved rinse arms

increases initial response by 30% and rotation speed by 20%

Insulated boiler

lowers running costs and improves boiler recovery times

Standby mode

reduces power usage when not in use

Operation

Intuitive, digital controls

reduces user error and staff training

EasyClean filters

maintenance friendly filters protect critical components

Chemical auto-dosing

eliminates user intervention and prevents over or under dosing

Auto drain down (optional)

ensures rapid drain down with no need for user intervention

Integral water softener (optional)

softens water without the need for an external unit

'Welcome to a cleaner world'

Standard Extra Range Glasswasher Specifications



	SXG40	SXG45	SXG50
Cycle time	60 90 120 180 User Defined	60 90 120 180 User Defined	60 90 120 180 User Defined
Baskets (x2)	400 x 400 mm	450 x 450 mm	500 x 500 mm
Height	690 mm	690 mm	690 mm
Width	475 mm	525 mm	575 mm
Depth	540 mm	545 mm	605 mm
Depth with door open	885 mm	890 mm	950 mm
Usable wash height	290 mm	310 mm	320 mm
Drain height	120 mm	120 mm	120 mm
Drain Ø	25 mm	25 mm	25 mm
Wash tank	18 lts	18 lts	20 lts
Boiler	2.8 lts	2.8 lts	2.8 lts
Water usage	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c
Wash element	1.6 kW	1.6 kW	1.6 kW
Boiler element	2.8 kW	2.8 kW	2.8 kW
Total load	4.7 kW	4.7 kW	4.7 kW
Amps required	20 Amps**	20 Amps**	20 Amps**
Detergent dosing	Yes	Yes	Yes
Rinse aid dosing	Yes	Yes	Yes
Water connection	3/4 BSP	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar	2-4 bar
Required water flow rate	10 lts p/min	10 lts p/min	10 lts p/min
Drain pump	Optional	Optional	Optional
Internal softener*	Optional	Optional	Optional

Where water hardness exceeds 100ppm a water softener is required.

* Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 125 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

** Can be configured to operate on either 13A or 3Ph+N upon request.

Warranty: Two years parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

